

V-belt

PU80A orange smooth

notched version possible 



FDA
EC
USDA









Order No.	Profile dimension mm	Cross section cm ²	approx. weight kg/100 m	Standard Roll		Recommended Min. pulley Ø		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBJ6YOG	6 x 4 (Y)	0,19	2,3	30	100	40	1,6	6,2	13,7
FBJ8MOG	8 x 5 (M)	0,32	4,0	30	100	45	1,8	10,3	22,6
FBJ10ZOG	10 x 6 (Z)	0,48	6,0	30	100	55	2,2	15,4	33,9
FBJ13AOG	13 x 8 (A)	0,82	10,0	30	100	85	3,3	26,3	57,9
FBJ17BOG	17 x 11 (B)	1,46	18,0	30	100	110	4,3	46,9	103,1
FBJ22COG	22 x 14 (C)	2,40	29,0	30	100	150	5,9	77,0	169,5
FBJ32DOG	32 x 20 (D)	5,00	62,0	30	100	220	8,7	160,5	353,1

Recommended pretension 4...8 %, **Coef. of friction μ** : Steel: approx. 0,65 | PE: approx. 0,35 | HDPE: approx. 0,30

approx. 84° Shore A

FDA/EC/USDA compliant

Symbols

							
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces. EC/FDA/USDA conformity for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY). Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for microorganisms