


## T-Profile

### T-Profile PU85A white or sapphire blue (20 x 8 mm)



Order No.	Profile dimension mm	Cross section cm <sup>2</sup>	approx. Weight kg/100 m	Standard Roll		Recommended Min. pulley $\varnothing$		Fmax/belt (Standard)	
				m	ft	mm	inch	kg	lbs
FBSP85A20X8W (white)	20x8	0,83	10,0	30	100	100	4,0	21,4	47,1
FBSP85A20X8 (sapphire blue)	20x8	0,83	10,0	30	100	100	4,0	21,4	47,1



Recommended pretension: 3...6 %, **Coeff. of friction  $\mu$** : Steel: approx. 0,60 | PE: approx. 0,35 | HDPE: approx. 0,30

approx. 88° Shore A

FDA/EC/USDA compliant

### Symbols

				 	 		
Antistatic profile with outstanding mechanical properties.	Profile with exceptional low-temperature flexibility down to -30°C.	Patented material formulation „PLUS“ for lower product elongation.	Very good UV resistance.	FDA/EC conformity for hydrolysis-resistant conveying profiles with rough and finely textured surfaces.  EC/FDA/USDA conformity for smooth profiles.	Metal and X-ray detectable profiles for maximum food safety.	Hydrolysis resistance (HY).  Suitable for humid environments.	Microbe-resistant materials do not provide a breeding ground for micro-organisms